

MODELO	DESCRIÇÃO	PÇ. UNIT.
--------	-----------	-----------

**POWERGRIP - YG2**

**950 €**



ELECTRICAL CHARACTERISTICS

Voltage 190 – 256V  
Capacity (at 230V) 3.680W  
Rated current 16A

PROTECTED LINES

220V AC Sockets - 6  
AC line types Analog, Digital, High Current  
COAX lines 1

PROTECTION PARAMETERS

Emergency limits  $\leq 190 \pm 4V$  /  $\geq 256 \pm 4V$   
Peak current 65.000A

SETUP AND CONTROL

Manual control Multifunctional button on face-plate and touch sensor  
ON/OFF scenarios Adjustment of delays between socket groups  
12V trigger IN / OUT  
RS232 integration Control4, Crestron, AMX etc.

PACKAGE INCLUDES

AC power cord 1.5 m (optionally – 3 m)  
19" rack mounts Included

GENERAL DATA

Faceplate material Brushed 4mm aluminum  
Overall dimensions (WxHxD) 440 x 80 x 185 mm  
Weight 4.8 kg

**POWERGRIP - YG3**

**2 450 €**

**NOVO**



- The most reliable protection against surges and high voltages.
  - Customizable filter technology.
  - Protection against threats received via antenna cables.
  - Wide operating voltage range.
- Multi function display screen with a choice of many colours, styles and fonts. Display can be dimmed or switched off if required.
  - 7 front panel touch buttons for control and configuration.
  - Mobile application for management and control, working over Wi-Fi.
- RS232 trigger input and output and optional Ethernet connection for professional control systems.