

# ITALIAN STAGE

ITALIAN  
**STAGE**



[www.italianstage.com](http://www.italianstage.com)



# ITALIAN STAGE

The new budget brand for sound systems products, has been created out of the vast experience that Proel has in this field.

The use of the most advanced Research and Development processes, normally reserved for much higher end products, efficient and strictly controlled quality assurance, as well

as a proven track record in ODM projects are just some of the elements characterizing the "budget/quality" mission of Italian Stage. A business opportunity to capture a market position with highly competitive, inherently reliable products without direct competitive comparison but at a similar price range.





# MIXERS

The new Italian Stage 2MIX is small format mixers' series offering everything the musician or the simple enthusiast need, as well as a clear and powerful sound thanks to the use of low noise preamps. Equipped with a complete feature set, the 2MIX

## IS 2MIX3UB



- Compact Design
- 1 MIC IN, 1 LINE IN, 1 Stereo IN
- Integrated ECHO effects
- Integrated USB 2 + 2 Interface
- Integrated Bluetooth

## New IS 2MIX4PRO



- 1 Master Fader
- XLR Outputs
- 3 Channel Fader
- 2 MIC IN, 1 STEREO LINE IN
- Integrated DSP MultiFX processor
- Phantom 48 V
- Hi-Z function
- Low Cut Filter
- Integrated USB Player / Recorder
- Integrated Bluetooth

## New IS 2MIX6PRO



- 1 Master Fader
- XLR Outputs
- 5 Channel Fader
- 4 MIC IN, 1 STEREO LINE IN
- Integrated DSP MultiFX processor
- Phantom 48 V
- Hi-Z function
- Low Cut Filter
- Integrated USB Player / Recorder
- Integrated Bluetooth



series offers Bluetooth audio streaming, as well as USB recording and playback. Equipped with a digital DSP Multi FX REVERB processor, the Italian Stage 2MIX lineup also works as a 2 + 2 channel USB audio interface for DAW recording / playback. The 4, 6 and

8 channel models also include USB audio with an integrated recorder / player able to record MP3 files directly on USB flash drives. You can play MP3 files as backing tracks, or play background music during live breaks.

## IS 2MIX8PRO



- |                                   |                                  |
|-----------------------------------|----------------------------------|
| 2 Master Fader                    | 1 Aux send                       |
| 1 Effect Fader                    | 5 Band Master Graphic EQ         |
| 7 Channel Fader                   | MUTE and PFL buttons             |
| 6 MIC / LINE IN, 1 STEREO LINE IN | Integrated USB Player / Recorder |
| Integrated DSP MultiFX processor  | Integrated Bluetooth             |
| Phantom 48 V                      | Sizes 340 x 380 x 50 mm          |
| 3 Band EQ on input channels       |                                  |



## New IS 2MIX8PRO



- |                                    |
|------------------------------------|
| 2 Master Fader                     |
| 1 Effect Fader                     |
| 11 Channel Fader                   |
| 10 MIC / LINE IN, 1 STEREO LINE IN |
| Integrated DSP MultiFX processor   |
| Phantom 48 V                       |
| 3 Band EQ on input channels        |
| 1 Aux send                         |
| 5 Band Master Graphic EQ           |
| MUTE and PFL buttons               |
| Integrated USB Player / Recorder   |
| Integrated Bluetooth               |



# LOUDSPEAKERS

## IS SPX08A



|                           |                                      |
|---------------------------|--------------------------------------|
| <b>Description</b>        | 8" bi-active two way plastic speaker |
| <b>Woofers</b>            | 8" VC 1,5"                           |
| <b>Driver</b>             | 1" VC 1"                             |
| <b>Line output</b>        | XLR OUT + ¼" JACK OUT                |
| <b>Line input</b>         | XLR IN + 2 x RCA                     |
| <b>Mic input</b>          | XLR IN + ¼" JACK IN                  |
| <b>Rms power</b>          | AB class 120 + 30 W                  |
| <b>Peak power</b>         | 300W                                 |
| <b>Frequency response</b> | 60hz-20khz                           |
| <b>Peak spl</b>           | 123 dB                               |
| <b>Power supply</b>       | AC110V/AC230V                        |

## IS SPX10A



|                           |                                       |
|---------------------------|---------------------------------------|
| <b>Description</b>        | 10" bi-active two way plastic speaker |
| <b>Woofers</b>            | 10" VC 1,5"                           |
| <b>Driver</b>             | 1" VC 1"                              |
| <b>Line output</b>        | XLR OUT + ¼" JACK OUT                 |
| <b>Line input</b>         | XLR IN + 2 x RCA                      |
| <b>Mic input</b>          | XLR IN + ¼" JACK IN                   |
| <b>Rms power</b>          | AB class 120 + 30 W                   |
| <b>Peak power</b>         | 300W                                  |
| <b>Frequency response</b> | 55hz-20khz                            |
| <b>Peak spl</b>           | 125 dB                                |
| <b>Power supply</b>       | AC110V/AC230V                         |

## IS SPX12A



|                           |                                       |
|---------------------------|---------------------------------------|
| <b>Description</b>        | 12" bi-active two way plastic speaker |
| <b>Woofers</b>            | 12" VC 2"                             |
| <b>Driver</b>             | 1" VC 1"                              |
| <b>Line output</b>        | XLR OUT + ¼" JACK OUT                 |
| <b>Line input</b>         | XLR IN + 2 x RCA                      |
| <b>Mic input</b>          | XLR IN + ¼" JACK IN                   |
| <b>Rms power</b>          | AB class 170 + 30 W                   |
| <b>Peak power</b>         | 400W                                  |
| <b>Frequency response</b> | 48hz-20khz                            |
| <b>Peak spl</b>           | 127 dB                                |
| <b>Power supply</b>       | AC110V/AC230V                         |

## IS SPX15A



|                           |                                       |
|---------------------------|---------------------------------------|
| <b>Description</b>        | 15" bi-active two way plastic speaker |
| <b>Woofers</b>            | 15" VC 2,5"                           |
| <b>Driver</b>             | 1" VC 1"                              |
| <b>Line output</b>        | XLR OUT + ¼" JACK OUT                 |
| <b>Line input</b>         | XLR IN + 2 x RCA                      |
| <b>Mic input</b>          | XLR IN + ¼" JACK IN                   |
| <b>Rms power</b>          | AB class 170 + 30 W                   |
| <b>Peak power</b>         | 400W                                  |
| <b>Frequency response</b> | 45hz-20khz                            |
| <b>Peak spl</b>           | 130 dB                                |
| <b>Power supply</b>       | AC110V/AC230V                         |



## IS SPX08AUB



**W** Wireless Audio System

|                    |                                                                          |
|--------------------|--------------------------------------------------------------------------|
| Multimedia player  | Usb Flash Drive, Sd Memory Card, Stereo Bluetooth Device, Remote Control |
| Description        | 8" bi-active two way plastic speaker                                     |
| Woofers            | 8" VC 1,5"                                                               |
| Driver             | 1" VC 1"                                                                 |
| Line output        | XLR OUT + ¼" JACK OUT                                                    |
| Line input         | XLR IN + 2 x RCA                                                         |
| Mic input          | XLR IN + ¼" JACK IN                                                      |
| Rms power          | AB class 120 + 30 W                                                      |
| Peak power         | 300W                                                                     |
| Frequency response | 60hz-20khz                                                               |
| Peak spl           | 123 dB                                                                   |
| Power supply       | AC110V/AC230V                                                            |

## IS SPX10AUB



|                    |                                                                          |
|--------------------|--------------------------------------------------------------------------|
| Multimedia player  | Usb Flash Drive, Sd Memory Card, Stereo Bluetooth Device, Remote Control |
| Description        | 10" bi-active two way plastic speaker                                    |
| Woofers            | 10" VC 1,5"                                                              |
| Driver             | 1" VC 1"                                                                 |
| Line output        | XLR OUT + ¼" JACK OUT                                                    |
| Line input         | XLR IN + 2 x RCA                                                         |
| Mic input          | XLR IN + ¼" JACK IN                                                      |
| Rms power          | AB class 120 + 30 W                                                      |
| Peak power         | 300W                                                                     |
| Frequency response | 55hz-20khz                                                               |
| Peak spl           | 125 dB                                                                   |
| Power supply       | AC110V/AC230V                                                            |

## IS SPX12AUB



**W** Wireless Audio System

|                    |                                                                          |
|--------------------|--------------------------------------------------------------------------|
| Multimedia player  | Usb Flash Drive, Sd Memory Card, Stereo Bluetooth Device, Remote Control |
| Description        | 12" bi-active two way plastic speaker                                    |
| Woofers            | 12" VC 2"                                                                |
| Driver             | 1" VC 1"                                                                 |
| Line output        | XLR OUT + ¼" JACK OUT                                                    |
| Line input         | XLR IN + 2 x RCA                                                         |
| Mic input          | XLR IN + ¼" JACK IN                                                      |
| Rms power          | AB class 170 + 30 W                                                      |
| Peak power         | 400W                                                                     |
| Frequency response | 48hz-20khz                                                               |
| Peak spl           | 127 dB                                                                   |
| Power supply       | AC110V/AC230V                                                            |

## IS SPX15AUB



|                    |                                                                          |
|--------------------|--------------------------------------------------------------------------|
| Multimedia player  | Usb Flash Drive, Sd Memory Card, Stereo Bluetooth Device, Remote Control |
| Description        | 15" bi-active two way plastic speaker                                    |
| Woofers            | 15" VC 2,5"                                                              |
| Driver             | 1" VC 1"                                                                 |
| Line output        | XLR OUT + ¼" JACK OUT                                                    |
| Line input         | XLR IN + 2 x RCA                                                         |
| Mic input          | XLR IN + ¼" JACK IN                                                      |
| Rms power          | AB class 170 + 30 W                                                      |
| Peak power         | 400W                                                                     |
| Frequency response | 45hz-20khz                                                               |
| Peak spl           | 130 dB                                                                   |
| Power supply       | AC110V/AC230V                                                            |

# LOUDSPEAKERS

## IS X212AUB



**W** Wireless Audio System

## IS X215AUB



|                    |                                                                   |
|--------------------|-------------------------------------------------------------------|
| Multimedia player  | Usb Flash Drive, Sd Memory Card, Bluetooth Device, Remote Control |
| Woofers            | 12" VC 2"                                                         |
| Driver             | 1" VC 34 mm                                                       |
| Line output        | XLR OUT + 1/4" JACK OUT                                           |
| Line input         | XLR IN + 2 x RCA                                                  |
| Mic input          | XLR IN + 1/4" JACK IN                                             |
| Rms power          | AB class 350 + 50 W                                               |
| Peak power         | 800W                                                              |
| Frequency response | 48hz-20khz                                                        |
| Peak spl           | 129 dB                                                            |
| Power supply       | AC110V/AC230V                                                     |

|                    |                                                                   |
|--------------------|-------------------------------------------------------------------|
| Multimedia player  | Usb Flash Drive, Sd Memory Card, Bluetooth Device, Remote Control |
| Woofers            | 15" VC 2,5"                                                       |
| Driver             | 1" VC 34 mm                                                       |
| Line output        | XLR OUT + 1/4" JACK OUT                                           |
| Line input         | XLR IN + 2 x RCA                                                  |
| Mic input          | XLR IN + 1/4" JACK IN                                             |
| Rms power          | AB class 350 + 50 W                                               |
| Peak power         | 800W                                                              |
| Frequency response | 45hz-20khz                                                        |
| Peak spl           | 131 dB                                                            |
| Power supply       | AC110V/AC230V                                                     |





# SUBWOOFERS

## IS S112A



|                           |                                               |
|---------------------------|-----------------------------------------------|
| <b>Description</b>        | 12" WOODEN SUBWOOFER, 2 CHANNELS INPUT&OUTPUT |
| <b>Woofer</b>             | 12"                                           |
| <b>RMS Power</b>          | 350W CLASS AB Amplifier                       |
| <b>Peak power</b>         | 700W                                          |
| <b>Frequency response</b> | 40Hz-120Hz                                    |
| <b>Peak spl</b>           | 126 dB                                        |
| <b>Power supply</b>       | AC110V/AC230V                                 |

## IS S115A



|                           |                                               |
|---------------------------|-----------------------------------------------|
| <b>Description</b>        | 15" WOODEN SUBWOOFER, 2 CHANNELS INPUT&OUTPUT |
| <b>Woofer</b>             | 15"                                           |
| <b>RMS Power</b>          | 350W CLASS AB Amplifier                       |
| <b>Peak power</b>         | 700W                                          |
| <b>Frequency response</b> | 20Hz-120Hz                                    |
| <b>Peak spl</b>           | 128 dB                                        |
| <b>Power supply</b>       | AC110V/AC230V                                 |

## IS S118A



|                           |                                               |
|---------------------------|-----------------------------------------------|
| <b>Description</b>        | 18" WOODEN SUBWOOFER, 2 CHANNELS INPUT&OUTPUT |
| <b>Woofer</b>             | 18"                                           |
| <b>RMS Power</b>          | 350W CLASS AB Amplifier                       |
| <b>Peak power</b>         | 700W                                          |
| <b>Frequency response</b> | 20Hz-120Hz                                    |
| <b>Peak spl</b>           | 129 dB                                        |
| <b>Power supply</b>       | AC110V/AC230V                                 |

# PORTABLE SYSTEMS

## IS FRX08AW



|                    |                                                                                                                         |
|--------------------|-------------------------------------------------------------------------------------------------------------------------|
| Description        | 8" portable speaker with battery, MP3 player, SD card, USB, Stereo Bluetooth, 1 VHF wireless microphone, remote control |
| Woofer             | 8"                                                                                                                      |
| Horn driver        | 1"                                                                                                                      |
| RMS Power          | 30W Class D Amplifier                                                                                                   |
| Peak power         | 60W                                                                                                                     |
| Sensitivity 1W/1m  | 88dB                                                                                                                    |
| Frequency response | 50hz-18khz                                                                                                              |
| Power supply       | AC110V/AC230V                                                                                                           |

## IS FRX10AW



|                    |                                                                                                                          |
|--------------------|--------------------------------------------------------------------------------------------------------------------------|
| Description        | 10" portable speaker with battery, MP3 player, SD card, USB, Stereo Bluetooth, 1 VHF wireless microphone, remote control |
| Woofer             | 10"                                                                                                                      |
| Horn driver        | 1"                                                                                                                       |
| RMS Power          | 50W Class D Amplifier                                                                                                    |
| Peak power         | 100W                                                                                                                     |
| Sensitivity 1W/1m  | 90dB                                                                                                                     |
| Frequency response | 40Hz-18kHz                                                                                                               |
| Power supply       | AC110V/AC230V                                                                                                            |

## IS FR12AWV2



|                    |                                                                                                                                              |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Description        | 12" portable speaker with battery, MP3 player, SD card, USB, Stereo Bluetooth, 2 x UHF wireless microphone ( 863 - 865 Mhz ), remote control |
| Woofer             | 12"                                                                                                                                          |
| Horn driver        | 1"                                                                                                                                           |
| RMS Power          | 100W Class D Amplifier                                                                                                                       |
| Peak power         | 200W                                                                                                                                         |
| Sensitivity 1W/1m  | 92dB                                                                                                                                         |
| Frequency response | 40hz-18khz                                                                                                                                   |
| EQ                 | 5 band Graphic EQ                                                                                                                            |
| Power supply       | AC110V/AC230V                                                                                                                                |

## *New* IS FR15AWV2



|                    |                                                                                                                            |
|--------------------|----------------------------------------------------------------------------------------------------------------------------|
| Description        | 15" portable speaker with battery, MP3 player, SD card, USB, STEREO bluetooth, 2 x UHF wireless microphone (863 - 865 Mhz) |
| Woofer             | 15"                                                                                                                        |
| Horn driver        | 1"                                                                                                                         |
| RMS Power          | 100W Class D Amplifier                                                                                                     |
| Peak power         | 200W                                                                                                                       |
| Sensitivity 1W/1m  | 92dB                                                                                                                       |
| Frequency response | 38hz-18khz                                                                                                                 |
| EQ                 | 5 band Graphic EQ                                                                                                          |
| Power supply       | AC110V/AC230V                                                                                                              |

# COVERS



## **IS COVERFRX08**

Protection cover for SPX08A - SPX08AUB - FRX08AW

## **IS COVERFRX10**

Protection cover for SPX10A - SPX10AUB - FRX10AW

## **IS COVERSPX12**

Protection cover for SPX12A - SPX12AUB

## **IS COVERSPX15**

Protection cover for SPX15A - SPX15AUB



## **IS COVERS112**

Protection cover for S112A

## **IS COVERS115**

Protection cover for S115A

## **IS COVERS118**

Protection cover for S118A





**ITALIAN**  
**STAGE**

**is a brand of**  
PROEL SPA  
(Worldwide Headquarters)  
Via alla Ruenia, 37/43  
64027 Sant'Omero (TE) - ITALY  
Tel. +39 0861 81241  
Fax +39 0861 887862  
P.I. 00778590679  
N.Reg.AEE IT 0802000002762

**IS CAT24IE**

[www.italianstage.com](http://www.italianstage.com)